

PREMIER LOCKERS



PREMIER LOCKERS

TWO COMPARTMENT LOCKERS

Height 1775 mm ,Widths 225 mm ,300 mm, 380 mm, 450 mm, Depths 300 mm, 380 mm , 450 mm

Sturdy Construction: Door frame constructed from heavy gauge mild steel of press formed channel section.

Door Strength: Full length door stiffeners for extra door rigidity and 'five knuckle' semi-concealed hinges.

Style: Attractive and functional locker design.

Colour: Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Compartment Size: Each compartment opening size 810 mm high (internal 847 mm), width and depth as above.

Nesting: Lockers can be supplied as single units or nested in groups during the manufacturing process.

All lockers are holed in back and sides to enable them to be bolted together into rows or back to back to suit your requirements. **Note:** When preparing locker room layouts allow approximately 4 mm extra for each nest for rivet heads at the sides of lockers in each row.

Construction: Spot welded and pop riveted.

Material: Mild steel Powder Coated.

Door Frame Assembly: Comprising two uprights manufactured from heavy gauge mild steel of press formed channel

section; top and bottom cross members which are designed to create door stops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.

Doors: Doors are attached to the right hand side of door frame upright with two 'five knuckle' semiconcealed hinges per door. Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder. The inside of the door has a full length vertical 'stiffener' to provide greater rigidity. Two rubber buffers are fitted to the top and bottom corners of each door for quiet closure.

#

Bottom: The bottom is formed as a 60 mm high plinth. All edges have return bends and the front and rear edges drilled for fitting to stands or stands with seat.

Hook & Hanger Rails: A coat hook is located each side of the main compartment under the shelf; for lockers over

300 mm deep a plastic coated clothes hanger rail is also fitted.

Locking: Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Premier Lockers.

We can also supply, as an optional extras, a wide range of locking options, Numbering, Sloping tops, please ask for details.